



AMTE-300

TILT ADJUSTABLE ASSEMBLY TABLE

AMTE-300 FEATURES

- DESIGNED FOR QUICK, SAFE, AND EASY MOUNTING FOR ANY TYPE OF MANUFACTURING/ASSEMBLY PROCESS
- TILT-ADJUSTABLE WITH VARIABLE WORKING HEIGHT
- AN EXTENDED LINE OF ACCESSORIES
- MAXIMUM WORKING WEIGHT – 400 KG / 908 LB
- ERGONOMIC AND HIGHLY ACCESSIBLE
- DESIGNED TO REDUCE POTENTIAL FOR WORKPLACE INJURY

MADE IN

U. S. A.



AMTE SERIES ASSEMBLY TABLES

SPECIFICATIONS

AMTE-300

AMTE-400

	AMTE-300	AMTE-400
Product Number	31013.US	31014.US
Backplane and enclosure door clamping system	✓	✓
Tilt adjustment	✓	✓
Height adjustment		✓
Electric Motor	✓	✓
Battery Operation	Optional PN: 31013-002	Optional PN: 31013-002
Adjustable angle of inclination	0-70°	0-70°
Working height	33.5" x 35.5" (851 mm x 901 mm)	32" x 46" (813 mm x 1168 mm)
Floor Mountable Leveling Pad Base	✓	Optional PN: 31003-006
Caster Wheel Base	Optional PN: 31003-025 (2x); 31003-010 (2x)	✓
Max. size surface area (W x H)	44" x 78" (1118 mm x 1981 mm)	44" x 78" (1118 mm x 1981 mm)
Max. size surface area with table extensions (W x H)	80.5" x 83.5" (2045 mm x 2121 mm)	80.5" x 83.5" (2045 mm x 2121 mm)
Maximum work load	908 lb (400 kg)	908 lb (400 kg)
Table Footprint	60" x 41" (1524 mm x 1041 mm)	60" x 41" (1524 mm x 1041 mm)
Shipping Weight	540 lb (246 kg)	640 lb (291 kg)
Scope of delivery	AC operated tilt-adjustable table kit, Unassembled , Leveling pad base (x1), Standard clamping units (x4), AC powered actuator (x1), Controller keypad, battery (x1), Shipping crate (x1)	AC operated 2-axis tilt and height adjustable table assembly , Caster wheels (2 locking, 2 non-locking), Standard clamping units (x4), AC powered actuator (x1), Controller keypad, battery (x1), Shipping crate (x1)